


FS800A

18GHz, 50 Ohm, Φ 7.9mm, PFA Jacket, Flexible Cable. Solid Inner Conductor

Structure:



Structure Details:

Cable Type	Dia.(mm)	Material
Inner Conductor	2.30	Silver plated Copper
Dielectric	6.20	Low Density PTFE
Inner Shield	6.44	Silver Plated Copper Strip
Outer Shield	7.05	Silver Plated Copper Braid
Jacket	7.90	PFA

Electrical Specifications:

Operating Freq.: 18 GHz

Cut-off Freq.: 18 GHz

Impedance: 50 Ω

Velocity of Propagation: 83%

Shielding Effectiveness: >90 dB

Dielectric Withstanding Voltage: 3000 V DC

Passive Intermodulation (PIM): -155 dBc

Phase Change vs Temperature: <750PPM@-55~+85 °C

Mechanical Specifications:

Static Bending Radius: 39 mm

Dynamic Bending Radius: 79 mm

Weight: 130 g/m

Environmental Specifications:

Temperature: -55~+165 °C

Typical Attenuation(dB/100m) and Power handling (W)

Freq.(GHz)	1	2	3	6	8	10	12.4	16	18
Attenuation ¹	14.7	21	26	37.3	43.4	48.8	54.8	62.8	67
Avg. Power ²	2303	1614	1309	912	783	696	620	541	507
K1: 0.456300, K2: 0.000320									

1: Typical value@+25 °C, VSWR=1.0;

2: Typical value@+40 °C, atmospheric pressure;

3: Typical Cable Attenuation Calculation, Formula: $K1 \cdot \sqrt{F(\text{MHz})} + K2 \cdot F(\text{MHz})$;

4: Typical Connector Attenuation Calculation, Formula: $0.03 \cdot \sqrt{F(\text{GHz})}$.

Cable Assemblies Naming Rule:

PN: Cable-Max. Freq.-Conn.1-Conn.2-Length(m)

Eg.: FS800A-18-NM-NF-1 means FS800A cable, DC-18GHz, N (m)-N(f), 1m.