


FS2PD30-2000-8000-S

2-Way Power Divider / Combiner, 30W, 2-8GHz, SMA(f)

Electrical Specifications		
1	Frequency Range	2.0-8.0 GHz
2	Impedance	50 Ω
3	Insertion Loss	0.6 dB Max. (<i>Above 3.01 dB Theoretical Loss</i>)
4	Isolation	20 dB Min.
5	Input VSWR	1.30:1 Max.
6	Output VSWR	1.30:1 Max.
7	Phase Balance	$\pm 3^\circ$ Max.
8	Amplitude Balance	± 0.3 dB Max.
9	Power Handling @ Common Port	30 W CW (Divider Mode)
10	Power Handling @ Common Port	2 W CW (Combiner Mode)
Environmental Specifications		
1	Operating Temperature	-40°C ~ +70°C
Mechanical Specifications		
1	Connectors	SMA-Female (Passivated Stainless Steel)
2	Surface Finish	Black Paint
3	Dimensions ¹	28x28x10 mm [1.102x1.102x0.394 in]

Outline Drawing (Dimension in mm [in], Tolerance: ± 0.3 mm [± 0.01 in])



Ordering Information:

Model: **FS2PD30-2000-8000-S**

Note 1: Dimensions do not include connectors.