


FSCT2-18-S-C

Coaxial Termination, DC-18GHz, 2W, SMA(M)


Electrical Specifications					
1	Nominal Impedance	50 Ω			
2	Average Power ¹	2W @ 25°C			
3	Frequency Range	DC~4GHz	DC~8GHz	DC~12.4GHz	DC~18GHz
4	VSWR	≤1.10	≤1.20	≤1.20	≤1.25
Environmental Specifications					
1	Operating Temperature	-55°C~+125°C			
Mechanical Specifications					
1	Connectors	SMA(f)/SMA(m)			
2	Body Material	Passivated Stainless Steel			
3	Chain length	The length can be customized			

Note 1: Refer to the power derating curve for details.

Outline Drawing (Units: mm/[inch], Tolerance: ± 0.3 mm)



Outline A



Outline B

Ordering Information:

Model	Connector Type	Outline Drawing
FSCT2-18-S-C(L) ²	SMA-Female (default)	Outline A
FSCT2-18-SM-C(L) ²	SMA-Male	Outline B

Model: **FSCT2-XX-SM-CYY**

XX = Frequency Range (4GHz, 8GHz, 12.4GHz, 18GHz)

YY = Length(CM)

Example: 18GHz, SMA male, Chain 5cm→**FSCT2-18-SM-C5**

Note 2: L= Chain length in CM